A1-F18EA-GAI-000

1 December 2007

Change 23 - 15 July 2021

TECHNICAL MANUAL

ORGANIZATIONAL MAINTENANCE

GENERAL AIRCRAFT INFORMATION

NAVY MODEL F/A-18E/F AND EA-18G 165533 AND UP

<u>DISTRIBUTION STATEMENT C.</u> Distribution authorized to U.S. Government Agencies and their contractors to protect publications required for official use or for administrative or operational purposes only, determined on 15 August 2006. Other requests for this document shall be referred to Commander, Naval Air Systems Command (PMA-265), RADM William A. Moffett Bldg, 47123 Buse Rd, Bldg 2272, Patuxent River, MD 20670-1547.

<u>DESTRUCTION NOTICE</u> - For unclassified, limited documents, destroy by any method that will prevent disclosure of contents or reconstruction of the document.

Published by Direction of the Commander, Naval Air Systems Command

0801LP0010073

ORGANIZATIONAL MAINTENANCE

DANGER AREAS AND PRECAUTIONARY MEASURES

Reference Material

None

Alphabetical Index

Subject	Page No
Airframe and External Stores	2
Auxiliary Power Unit (APU)	2
Engine	2
Leading Edge Extension Spoiler	2
Minimum Safe Distances	3
Precautionary Measures	3
Radar Antenna AN/APG-73	3
Radiation	3
Stores and Armaments	2
Airframe and External Stores Danger Areas, Figure 3	14
APU Danger Areas, Figure 6	25
Canopy, Seat and DFIRS Explosive Devices	2
Crew Station Explosives	2
Canopy, Seat and DFIRS Explosive Devices, Figure 2	7
Engine Danger Areas, Figure 4	16
Flammable Liquids, Compressed Gases, and Explosive Devices	2
Flammable Danger Areas	2
Flammable Liquids, Compressed Gases and Explosive Devices, Figure 1	4
Noise Danger Area, Figure 5	21
Radiation Danger Areas and Minimum Safe Distance, Figure 8	27
Weapon, Radiation, and Failure Danger Areas, Figure 7	26
•	

Record of Applicable Technical Directives

None



A1-F18EA-GAI-000

1. FLAMMABLE LIQUIDS, COMPRESSED GASES, AND EXPLOSIVE DEVICES.

2. FLAMMABLE DANGER AREAS. Areas including reservoirs of flammable liquids, gases under pressure, and explosive devices are shown (figure 1). Rescue and maintenance personnel should be aware of the hazards related to these areas.

3. <u>CANOPY, SEAT AND DFIRS EXPLOSIVE</u> DEVICES.

- 4. CREW STATION EXPLOSIVES. Many explosive devices (figure 2) are located in and around the crew station. The ejection seat(s) have rocket motors, initiators, and controls that require special handling during ground operations. The canopy has rocket motors, initiators, thrusters, and controls that also require special handling.
- 5. The DFIRS impact initiator and the severable door (300) (figure 3) are explosive devices. They do not require special handling during ground operations but do require special maintenance handling.


6. AIRFRAME AND EXTERNAL STORES.

- 7. STORES AND ARMAMENTS. External fuel tanks, vertical ejection racks, missile launchers and conventional/nuclear weapons (figure 3), loaded on wing or fuselage centerline pylons may be ejected by explosive cartridges. The area near these devices must be considered hazardous for maintenance personnel when aircraft electrical power is on.
- 8. Missile exhaust areas and path of trajectory (figure 7) are hazardous for personnel. An inadvertently fired missile can cause death or injury from either end.
- 9. The M61A2 gun projectile trajectory path (figure 7) is hazardous to personnel. Gun fire can cause death or injury.
- 10. Aircraft carrying munitions must be loaded, unloaded, and parked in designated explosives parking areas.
- 11. LEADING EDGE EXTENSION SPOILER The leading edge extension (LEX) spoiler is a secondary flight control surface located on the

left/right LEX immediately forward of the leading edge of the wing and covers three engine inlet bleed system vents. The spoiler is controlled by electrical signals from the flight control computers and is hydraulically actuated. To prevent personnel injury, aircraft damage, or equipment damage, personnel must be kept clear of flight control surfaces. Flight control surfaces can move with hydraulic power applied.

- 12. ENGINE. Danger areas resulting from engine operation are related to exhaust velocity and temperature, air intake, and noise.
- 13. Air Intake and Exhaust. During ground operation of the engines, the forward and aft ends of the aircraft are danger areas (figure 4). In rushing air can pull a person into or against the intake ducts. Engine exhaust air can cause death or serious burns. The area immediately aft of the tail pipes is hazardous for 15 minutes after engine shutdown.
- 14. Engine Noise Danger. The noise level of operating jet engines can cause hearing loss. Relative noise levels (figure 5) are shown at various distances from aircraft. Ear protectors must be worn when working near operating engines.
- 15. Flammable or explosive materials, in or in contact with metallic containers, must not be left in rf energy fields.
- 16. Refueling must not be done within 100 feet of operating airborne type radio or air radar equipment or within 300 feet of ground radar equipment.
- 17. AUXILIARY POWER UNIT (APU). Danger areas resulting from APU operation are related to exhaust velocity and temperature, air intake, and noise.
- 18. Air Intake and Exhaust. Danger areas resulting from APU operation are shown (figure 6). The APU intake duct is in door 52. The APU exhaust duct is in door 302.
- 19. <u>Dangerous Noise Level.</u> Noise levels near APU intake and exhaust ports during operation may cause hearing loss. Ear protection must be worn when working near an operating APU.


IDLE POWER



EFN540-23-1-005

Figure 5. Noise Danger Area (Sheet 1 of 4)

MIL POWER




DISTANCE IN FEET

EFN540-23-2-005

Figure 5. Noise Danger Area (Sheet 2)

MAX POWER



DISTANCE IN FEET

		LLOWABI OUND LEV	The contract of		E RESPONSE)	. ×	
TYPE EAR	EXPOSURE TIME, HOURS PER DAY							
PROTECTIVE DEVICES	1/4	1/2	1	2	4	6	8	
NO PROTECTION	115	110	105	100	95	92	90	
EAR PLUGS WITH AVERAGE SEAL	127	122	117	112	107	104	102	
EAR PLUGS AND EARMUFFS	135	130	125	120	115	112	110	

EAR PROTECTIVE DEVICES

